

DMX

Isolator Splitter

leprecon.



LDMX-4 and LDMX-8

The LDMX ensures optically safe DMX line splitting and isolation of DMX-512. These handy DMX control tools can be rack mounted or used as a stand alone device. Accepts a DMX control signal from the console and provides isolation between the control input and additional DMX feeds for dimmer packs and racks, moving lights, color scrollers or foggers.

SPECIFICATIONS

Control Input

Male 5-pin XLR DMX

Pass Thru

Female 5-pin XLR DMX Unbuffered Pass Thru

Isolated Outputs

LDMX-4 1 x 4

Provides four isolated outputs

LDMX-8 1 x 8

Provides eight isolated outputs

Choose from 5 pin or 3 pin F XLR

DMX Termination

Switch provides termination of the DMX data link

LED Indication

Power Indicator

Valid DMX LED indication for isolated outputs

Power Input

IEC flush mounted male, power cord included. External switch for 110/220 volt operation

Overcurrent Protection

Miniature fuse, 5 x 20mm 2 amp. Inlet contains a spare fuse.

Dimensions

Standard E.I.A. rack mountable.

Height 1.75" Width 19" Depth 7".

Weight 8.75 lbs.

VISIT OUR WEBSITE www.leprecon.com

Leprecon a Subsidiary of CAE, Inc.

10087 Industrial Drive, P.O. Box 430, Hamburg, MI 48139-0430 USA, 810-231-9373, FAX 810-231-1631, Lepsls@leprecon.com